



# MOTOAMERICA TECHNICAL BULLETIN

## 01-2019

MotoAmerica approved "Superbike Kit"

The MotoAmerica approved "Superbike Kit" system will be based on the MoTeC M130 hardware. The firmware was designed by MoTeC UK and will be sold as a complete package including all activation codes, software, ignition drivers, lambda sensor, color display/logger at a reduced cost. Due to the special pricing and specifications provided by MotoAmerica the ECU will be locked and no other licenses will be available. The total cost is \$5852.44 + tax and will be available for purchase at any US MoTeC dealer. The units will receive a special part number (TBA) and will be available for purchase January 1, 2019. Replacement parts are available at normal retail price.

### MotoAmerica "Superbike Kit" Item List May only be purchased as a complete kit.

<i>Item Number</i>	<i>Unit</i>	<i>Ordered</i>	<i>Shipped</i>	<i>Back Ordered</i>	<i>Price</i>	<i>Amount</i>
MOTOAMERICA KIT PRICING						
M130 M	EACH	1.0000	0.0000	0.0000		
M1 MARINE ECU 60 POS PLASTIC						
23024	EACH	1.0000	0.0000	0.0000		
M130 ACTIVATION						
*MA ECU	EACH	1.0000	0.0000	0.0000		
INCLUDES LOGGING 2+3						
M IGN4	EACH	1.0000	0.0000	0.0000		
IGNITION DRIVE UP TO 4 COILS						
M LTC	EACH	1.0000	0.0000	0.0000		
LAMBDA TO CAN						
M C125 USB	EACH	1.0000	0.0000	0.0000		
18060 COLOR DISPLAY LOGGER USB						
M C125 ENABLE	EACH	1.0000	0.0000	0.0000		
C125 ENABLE CODE SN:						
M 0258 001	EACH	1.0000	0.0000	0.0000		
SENSOR LAMBDA LSU 4.9						
LOCKED TO SERIES, NO OTHER LICENSE IS AVAILABLE ON ECU						
All claims for errors or damage must be made within 5 days of receipt of goods. A 15% restocking charge will be made when goods are returned to us where no error on our part exists. No returns for any reason after 30 days. Past due amounts subject to a 1.5% per month service charge (18% per annum). All parts related to vehicle emissions or safety are sold for Off Highway racing use in unlicensed vehicles which may never be operated on public roads. See Us at: <a href="http://www.motec.com">http://www.motec.com</a>						Net Order: 5,852.44 Less Discount: 0.00 Freight: 0.00 Sales Tax: 0.00 <b>Order Total: 5,852.44 USD</b>
<b>All amounts are in U.S. Dollars</b>						



UPDATED 12.14.18



### FIRMWARE SUMMARY

---

MoTeC's Mid Level Superbike M1 ECU firmwares are based on the 2019 British Superbike Championship firmwares, but with the addition of extra rider aids (traction control, anti-wheelie, launch control and closed loop fueling) and the removal of certain BSB specific limitations (maximum engine speed limit, scrutineer logging, advanced security).

The packages allow for fully flexible operation of most four cylinder port injected motorcycle engines fitted with drive by wire systems. Apart from engine control, the packages also provide various rider aids, in line with the championship rules.

There are specific firmwares for each individual make and model that is entered into the championship. All firmwares are broadly similar, with only small differences from bike to bike according to the base model hardware specification.

#### ► GENERAL FEATURES

---

- Operates four cylinder port injected engines with two injectors per cylinder.
- Support for in-line or vee configurations.
- Supports stock engine synchronization methods i.e. cam sensor, intake depression.
- Odd-fire engines supported.

#### ► FUEL FEATURES

---

- Pulse volume fuel model (n/alpha).
- 3 axis Fuel Volume Main table (Engine Efficiency v Engine Speed v Driver Fuel Volume Main Switch).
- Fuel compensation tables for Coolant Temperature, Airbox Temperature and Airbox Pressure.
- Pulse compensation tables for primary and secondary injector interaction.
- Throttle rate of change transient fuel calculation.
- 2 axis individual cylinder trim tables (Engine Efficiency v Engine Speed).
- Closed loop fuel control based on a single lambda input.

### ► IGNITION FEATURES

---

- 3 axis Ignition Timing Main table (Engine Load v Engine Speed v Driver Ignition Timing Main Switch).
- Ignition compensation tables for Coolant Temperature, Airbox Temperature and Gear.
- 2 axis individual cylinder trim tables (Engine Load v Engine Speed).
- Knock control.

### ► CONTROL FEATURES

---

- Up to two drive by wire motors with 2 axis grip translation table for each gear (Throttle Grip Sensor v Engine Speed) and minimum positions from engine braking strategy and idle table.
- Support for exhaust servo motors.
- Top level gear shift strategy for upshifts and downshifts.
- Variable intake length control (BMW, Ducati, Yamaha).
- Variable fuel pressure control (BMW).

### ► RACE FEATURES

---

- Engine braking control via drive by wire minimum position. Open loop component for each gear (Engine Speed Calculated v Gear) and closed loop component based on target rear wheel slip (P controller).
- Launch control via ignition retard, engine speed limiting and throttle limiting. Activation based on throttle grip threshold and de-activation based on exit gear.
- Traction control via front and rear wheel speed comparison and aim slip. PID controller based on aim slip error. Power reduction by means of ignition cut or ignition retard.
- Anti-wheelie control intrinsic to traction control strategy. Wheelie state is determined using suspension position, state then determines whether to apply additional gain and minimum power reduction tables.
- Engine Overrun Fuel Trims selectable for individual cylinders.
- Lean angle determination via IMU, GPS or sensor.
- Lap timing via MoTeC BR2, switched input or GPS.
- SLM support.
- Rain light support.
- Tilt switch feature.



# MOTOAMERICA TECHNICAL BULLETIN

## 01-2019

---

### ▶ SUPPORTED NON-ENGINE SENSORS

---

- Brake Pressure Front/Rear.
- Clutch Position and Pressure.
- GPS via CAN.
- Multiple IMUs (Bosch MM5.10, E Lean, Yamaha R1).
- Steering Damper Position.
- Suspension Position Front/Rear.
- Wheel Speed Front/Rear.

Please contact [technicaldirector@motoamerica.com](mailto:technicaldirector@motoamerica.com) with any questions.



UPDATED 12.14.18

